

Important notes:

Do **NOT** write outside the grey boxes. Any text or images outside the boxes **will** be deleted.

Do **NOT** alter the structure of this form. Simply enter your information into the boxes. The form will be automatically processed – if you alter its structure your submission will not be processed correctly.

Do not include keywords – you can add them when you submit the abstract online.

Title:

The impact of green buildings accreditation on construction and demolition waste minimization: A study of Hong Kong Building Environment Assessment Method using big data

Authors & affiliations:

Chen Xi^{1,*}, Weisheng Lu¹, Hongdi Wang¹

¹ Department of Real Estate and Construction, The University of Hong Kong, Hong Kong, P.R. China

* Corresponding author. Tel: +852- 93863858, E-mail: chenx90@hku.hk

Full Paper: (Your paper must use **Normal style** and must fit in this box. Your paper should be no longer than 2500-9000 words. The box will 'expand' as you add text/diagrams into it.)

Abstract

Construction and demolition (C&D) waste often constitutes a prodigious portion of the total municipal solid waste in contributing to the environment degradation. C&D waste minimization, which is a sustainable activity for both environment and material resources, serves as an indispensable element of green building assessment systems worldwide. How green building accreditation impacts on C&D waste minimization is a valid and important research question for green building award applicants, policy-makers and other stakeholders, which was seldom studied using a quantitative approach. Therefore, this paper aims to quantify the waste minimization which existing green building assessment system can be used to achieve by analyzing a big dataset of C&D waste management recorded in five years (2011-2015) in Hong Kong. The waste generation rates are compared between buildings awarded with and without Hong Kong Building Environment Assessment Method (HK-BEAM) prizes to illustrate the impact of HK-BEAM on C&D waste minimization. The research findings will not only present accurately quantified effect on CWM led by green building accreditation, but also provide stakeholders with a reference for making strategies and policies on C&D waste management and green building.

Introduction

Construction activities have led to a considerable amount of construction waste worldwide. In United States, the building-related waste generation amount in 2003 was estimated to be 170 million tons, with 15 million tons for construction, 71 million tons for renovation and 84 million tons for demolition (EPA, 2009). European Commission (EC) reported the C&D waste is responsible for 25%-30% of all waste generated in the European Union (EC, 2015). Statistics show that solid waste ending up in Hong Kong landfills reached 14, 311 ton per day (tpd) in 2013, of which 25% or 3,591 tpd was from construction activities (Hong Kong Environment Protection Department [HKEPD], 2015a). Meanwhile, there have been warnings that the landfills in Hong Kong, planned to last until 2020, could be full several years earlier if nothing is conducted to reduce waste loads (HKEPD, 2015b). The promotion of sustainable development has exerted the demand for proper methods to focus on waste minimization in construction industry.

Management strategies and technologies have been studied so as to tackle the existing construction waste problems. From management perspectives, Poon et al. (2001) suggested enacting contractual requirements or legislation to make on-site waste sorting a long-term solution to the landfill shortage. Shen et al. (2004) developed a waste management mapping model, which assists in planning waste management procedures on construction sites. Lu and Yuan (2013) suggested the application of offshore prefabrication, which could lead to around 2% construction waste reduction. Osmani et al. (2008) recommended waste minimization design, which could lead to about one-third of construction waste. In addition, Wang et al. (2014) identified six critical factors that significantly influence the waste minimization at design stage. Technically, integrated GPS and GIS technology was investigated and found effective in minimizing the amount of onsite material wastage (Li et al., 2005). In addition, viable technologies on construction waste recycling were also reviewed by Tam and Tam (2006). Echoed with academia, Hong Kong governments also formulated relevant policies to promote construction waste minimization, among which, the Construction Waste Disposal Charging Scheme enacted since 2005 (HKEPD, 2015c) has been proved to be effective for construction waste reduction (Lu and Tam, 2013). Although numerous management

Important notes:

Do **NOT** write outside the grey boxes. Any text or images outside the boxes **will** be deleted.

Do **NOT** alter the structure of this form. Simply enter your information into the boxes. The form will be automatically processed – if you alter its structure your submission will not be processed correctly.

Do not include keywords – you can add them when you submit the abstract online.

strategies and technologies have been tested effective in C&D waste minimization, previous studies seldom investigated how one of the existing practices, green building accreditations where the requirements for waste minimization is an indispensable part impact on construction waste minimization. This paper quantifies the waste minimization which existing green building assessment systems can be used to achieve. The study starts with hypotheses of the relationship between green building accreditation and waste generation rate (WGR), which is a key performance indicator for C&D waste management. Then, the WGRs are compared between buildings awarded with and without Hong Kong Building Environment Assessment Method (HK-BEAM) prizes to illustrate the impact of HK-BEAM on construction waste minimization by analyzing a big dataset of CWM recorded in recent five years. The impact of green building accreditation on construction waste minimization is discussed based on the results from the comparison.

Hypothesis

1. Hypothesis 1 (H_1): The CWM performance of green building accreditation certificated buildings is better than ordinary buildings, which is reflected by the overall WGR of BEAM certificated projects are lower than the overall WGR of ordinary projects.
2. Hypothesis 2 (H_2): The CWM performance of green building accreditation certificated buildings are in the order of Platinum, Gold, Silver and Bronze, which will be reflected by their WGR.

Data Description

Until early 2015, BEAM plus has accepted the registration of 616 projects, the name and address of which are published online. A rating is issued to an assessed project according to the attained credits: Platinum, Gold, Silver, Bronze, or Unclassified. The distribution of the assessed projects is shown in Table 1. To effectively manage C&D waste, a Construction Waste Disposal Charging Scheme (CWDCS), which has come into in Hong Kong since December 2005. C&D works conducted in Hong Kong are required to open a billing account for afterward construction waste disposal records by noting down the details of the work to be conducted. There had been 26,566 billing accounts opened until 2 September 2015. For a construction project carried out by several contractors, there are several accounts for different types of works, including demolition, foundation and building, while some projects as a package deal might only have one account for all types of works. HKEPD have been recording the waste disposal information comprising account number, waste weight and other information of every lorry of C&D since the establishment of CWDCS. This study mainly relies on these second-hand data records. Until end of June 2015, this scheme had led to the generation of 5,871,539 waste disposal records at the Hong Kong Environment Protection Department (HKEPD). It can be seem in Fig. 1 the three database can be connect based on the account number.

Table 1 Distribution of BEAM assessed projects

Result	Platinum	Gold	Silver	Bronze	Unclassified
Number	35	62	35	42	77

Important notes:

Do **NOT** write outside the grey boxes. Any text or images outside the boxes **will** be deleted.

Do **NOT** alter the structure of this form. Simply enter your information into the boxes. The form will be automatically processed – if you alter its structure your submission will not be processed correctly.

Do not include keywords – you can add them when you submit the abstract online.

Account

Contract name

Contract sum

Site address

Department

Type of construction work

Detail of construction work

5000280	MAIN DRAINAGE CHANNEL YUEN LC	96596682	HA TSUEN AND LAM HAU TSUEN SECT	CEDE	Others	CIVIL/ DRAINAGE WORKS
5000281	CIVIL ENGINEERING IMPROVEMENT	22513688	YUE WAN ESTATE	Y	Others	IMPROVEMENT WORKS
5000282	TERM CONTRACT FOR SLOPE MAIN	18500000	EASTERN KOWLOON	HKH	Others	SLOPE WORKS
5000283	LABORATORY FITTING-OUT CONTRA	116880000	8 G/F RADIANT STORE HONG KONG	Y	Others	FITTING-OUT WORKS
5000284	DISTRICT TERM CONTRACT FOR TH	72900000	ND H.K. HOUSING AUTHORITIES HOME	HKH	Others	MAINTENANCE WORKS
5000285	TERM CONTRACT FOR GROUND IN	6980000	WLOON, NEW TERRITORIES AND OUT	...	Others	GROUND INVESTIGATION
5000286	ENGLISH SCHOOLS FOUNDATION P	22200000	HA ON SHAN AT AREA 808, ST1, S22	...	Building	...
5000287	FOOTBRIDGE ACROSS PO KONG VII	14938681	AGE ROAD	...	Building	...
5000288	DESIGN AND CONSTRUCTION OF JC	212974185	CK HILL 6	...	Building	...
5000289	DISTRICT TERM CONTRACT FOR
5000290	2004/2005 CONSTRUCTION CONTRA	83148053	ND 25 AT
5000291	MINOR WORKS FOR SAU MAU PING	1619945	2 OF SAU
5000292	HK DISNEYLAND RESORT PROJECT	8590097	RESORT
5000293	10-YEAR EXTENDED LANDSLIP PRE	28000000	NG ISLAND
5000294	OUTLYING ISLANDS REVENUE - SIAC	19700000	YAN SEW
5000295	...	4480000	B. BONHA
5000296	COMPLETION WORKS FOR MAIN CC	2252100	ND 80, LA
5000297	PROPOSED RESIDENTIAL, COMMER	654817378	SA, HO LA
5000298	MATERIALS TESTING SERVICES TER	16003105	CHUEN ST
5000299	CONSTRUCTION OF RADIOTHERAP	323600000	PRINCE
5000300	ESTATE TERM CONTRACT FOR THE	23500000	LAI YUE
5000301	808TEPA PRIVATE INDEPENDENT SC	161627320	FOLK ROV
5000302	DEMOLITION OF ABANDONED PIER	370000	JAGUNA V
5000303	CHUNG CHAU VILLAGE SEVERAGE	10888131	SEAS PE
5000304	MAIN CONTRACT WORKS FOR THE	307000000

Database for 616 projects having applied BEAM plus

Project no	Address	Location	Type	Developer/BEAM Pro	Tool	award
1	Building 11No. 15 Sci	IN.T.	Government	Hong Kong	Julian BOT	BEAM Plus Final Platinum
2	Hang Seng Area 54A	IN.T.	Government	Hang Seng	LAU Wing	BEAM Plus Final Platinum
3	DUNBAR PLM/23 Dunbar	IKLN	Residential	Sky Treasu	CHAN Chi K	BEAM Plus Final Platinum
4	The Open U/81 Chung H	IKLN	Government	The Open U	LEUNG Chi	BEAM Plus Final Platinum
5	Energizing 122 Hoi Bu	IKLN	Government	Civil Engi	YAM Chi Wa	BEAM Plus Final Platinum
6	Holiday InnNos. 77-85	H.K.	Hotel	Million We	MO Cheung	BEAM Plus Final Platinum
7	Hysan Place/500 Hennes	H.K.	Commercial	Hysan Deve	TSANG Siu	BEAM Plus Final Platinum
8	Marinella 9 Welfare	H.K.	Residential	K. Wah Real	CHENG Chi	BEAM Plus Final Platinum
9	Redevelopm	9-11 Tsing	Residential	HKSAR Gove	LEE Kin Si	BEAM Plus Final Gold
10	The Peak G/118 Peak	R.H.K.	Commercial	Hang Lung	CHAN Wai T	BEAM Plus Final Gold

Database for 26,566 projects

	A	B	C	D	E	F	G	H	I	J	K	L
	Facility	Date of transaction	Vehicle No.	Account No.	Chit No.	Time-in	Time-out	Waste depth (meter)	Weight-in (tonne)	Weight-out (tonne)	Net weight (tonne)	ified
1	TKO1375F	13/08/15	SV6*81	7005394	13227395	08:04	08:15	0.81	19.88	14.58	5.30	ified
2	TKO1375F	13/08/15	NZ3*2	7017114	10714978	08:05	08:14	1.03	20.69	15.36	5.33	
4	TKO1375F	13/08/15	JL8*4	7022181	14095174	08:05	08:18	0.70	22.54	16.33	6.21	
5	TKO1375F	13/08/15	NT1*03	7005393	13913661	08:06	08:12	1.07	20.85	16.37	4.48	
6	TKO1375F	13/08/15	J89*96	7021726	13507842	08:07	08:18	1.29	20.97	15.26	5.71	
7	TKO1375F	13/08/15	TK7*29	7021804	13911380	08:07	08:23	1.05	24.76	14.99	9.77	
8	TKO1375F	13/08/15	TD6*19	7005394	13227396	08:08	08:22	1.20	19.87	14.41	5.46	
9	TKO1375F	13/08/15	SU4*91	7005393	13769663	08:09	08:21	1.28	20.45	16.06	4.39	
10	TKO1375F	13/08/15	SL1*98	7021473	13343562	08:11	08:24	0.75	23.35	15.73	7.62	
11	TKO1375F	13/08/15	P12*71	7018732	12538819	08:11	08:23	1.10	21.66	15.92	5.74	
12	TKO1375F	13/08/15	LE3*5	7016571	10818524	08:14	08:28	0.49	23.47	16.37	7.10	
13	TKO1375F	13/08/15	TH3*33	7017114	10714980	08:15	08:27	0.86	21.69	15.48	6.21	
14	TKO1375F	13/08/15	HF1*96	7020554	13801297	08:18	08:30	1.17	22.05	14.89	7.16	

Database for 5,871,539 waste disposal records

Fig. 1 Connections between databases for billing account information, BEAM plus projects details, and waste disposal records

Data Analysis

1. Connecting BEAM projects database and billing account database

The first step is to connect the databases in Fig.1. This study tried to use automatic match between BEAM projects database and billing account information database using the following algorithm:

- (1) All the spaces and punctuations in the site addresses and contract name in both BEAM projects database (File 1) and billing account details (File 2) are deleted.
- (2) Any site address or contract name becomes an ordered set made of characters, i.e. a site address and a contract name for project i in File 1 is A_i and B_i respectively, a site address and a contract name in File 2 is C_j and D_j respectively.
- (3) The site addresses in File 1 are used to match the site addresses in File 2. The same is done for the contract name. If A_i include C_j or C_j include A_i , or B_i include D_j or D_j include B_i we think i and j could possibly be the same project. i and j are preliminary matched. There are more than 1,000 matched records.
- (4) All the preliminary matched projects are manually checked, and actually unmatched projects and repeated projects are deleted.
- (5) Finally 24 projects were finally matched.

Obviously, the sample size is too small to reflect the reality. This study then manually searched for the matched projects. Eventually, there are 229 projects matched among 251 assessed projects. However, some projects only have the information of either demolition or construction. In the analysis process, the projects having information of demolition will be selected for analyzing the impact of BEAM on demolition waste minimization, while those having information of both building and foundation are selected for analyzing the impact of BEAM on construction waste minimization.

2. Estimating WGRs of BEAM assessed projects and ordinary projects

This study analyzed the waste generation rates (WGRs) of the BEAM assessed projects using the big dataset and the relevant databases shown in Fig. 1. Since the attainable credits for demolition waste reduction and construction waste reduction are set separately in the assessment, the WGRs of demolition and construction are measured separately. For demolition work alone, the corresponding billing account should only include demolition type, while construction works includes more kinds of works, mainly foundation and building. For demolition of a project, the WGR is calculated in Equation (1). For

Important notes:

Do **NOT** write outside the grey boxes. Any text or images outside the boxes **will** be deleted.

Do **NOT** alter the structure of this form. Simply enter your information into the boxes. The form will be automatically processed – if you alter its structure your submission will not be processed correctly.

Do not include keywords – you can add them when you submit the abstract online.

construction of a project, the WGR is calculated in Equation (2)

$$WGR_d = \frac{\text{total waste amount by weight} \times \text{contract sum}}{\text{total waste amount from foundation + total waste amount from demolition}} \quad (1)$$

$$WGR_c = \frac{\text{contract sum of foundation + contraction sum of demolition}}{\text{total waste amount from foundation + total waste amount from demolition}} \quad (2)$$

Big data in C&D waste management has shown a picture that the distribution of WGRs of a large number of construction projects is similar to a lognormal distribution rather than a normal distribution (Lu et al., 2015; Chen et al., 2015). Therefore, this study select median of a set of WGRs as a representative value to reflect the waste generation of that set of construction projects. This study first measured the overall WGR of demolition work and overall WGR of construction work for BEAM classified projects (i.e. Classified overall in Tables 2 and 3). Then, the WGRs of ordinary projects, which exclude the assessed projects, are measured as well to testify H_1 . In order to testify H_2 , the waste management performance of Platinum, Gold, Silver Bronze and Unclassified BEAM assessed projects are calculated separately and shown in Tables 2 and 3 for demolition and construction works. It can be seen in Table 2 the demolition WGRs is in accordance with both H_1 and H_2 , while Table 3 gives evidences to reject both H_1 and H_2 . For demolition on one hand, the WGRs of projects with various results from platinum to unclassified increase smoothly. The classified overall WGR is obviously less than WGR of ordinary projects. Beside, unclassified projects have less WGR than ordinary projects. On the other hand, no patterns can be found in the WGRs of construction works. Overall, it is obvious that the WGR_d for demolition are higher than those for construction works to a large extent.

Table 2 Median WGR (t/mHK\$) of demolition works

Type	Platinum	Gold	Silver	Bronze	Unclassified	Classified overall	Ordinary
WGR_d	255.56	322.01	384.38	457.55	508.43	340.48	588.36

Table 3 Median WGR (t/mHK\$) of construction works

Type	Platinum	Gold	Silver	Bronze	Unclassified	Classified overall	Ordinary
WGR_c	57.65	29.20	34.12	48.69	29.19	43.64	34.33

Discussion

1. Demolition waste reduction explanation

The waste management of overall BEAM awarded projects performs better than ordinary projects, because the WGR of former accounts for only 57.87% of the latter, which can be interpreted as 42.13% demolition waste minimization can be achieved in a project with the promotion of BEAM plus award. In BEAM plus, it is not only required to conduct a demolition waste management plan, but also two attainable credits are allocated for demolition waste recycling. For more than 30% demolition waste recycling, an assessed project can obtain one credit; for more than 60% recycling, the project can obtain two credits. The waste management plan and the credits for demolition waste recycling may be the reason that demolition waste management for the classified projects are largely performed better than ordinary project. For different results from platinum to unclassified, the demolition waste are managed in the order of best to worst, because contractors pay more efforts to get any credits, including demolition waste reduction in the green building scheme. The requirements for the credits may be easy to meet, because the waste generation from a demolition work is of tremendous amount, where over 90% of waste materials are inert waste with large potential for recycling (HKEPD, 2015). Nevertheless, BEAM might not be the only cause of the pattern of WGRs, waste reduction can also bring economic benefits for contractors, including the materials purchase cost, waste transportation cost, and waste disposal cost.

2. Construction waste reduction explanation

Though construction waste management plan is required and construction waste reduction is allocated with two credits as well, the waste management performance failed to show similar pattern with demolition waste management. As BEAM is not the only reason for demolition waste reduction, the no pattern for construction waste management performance can be explained by comparing the natures between demolition waste reduction and construction waste reduction. For ordinary project, the demolition waste generation can be roughly estimated as over 17 times of construction waste generation.

Important notes:

Do **NOT** write outside the grey boxes. Any text or images outside the boxes **will** be deleted.

Do **NOT** alter the structure of this form. Simply enter your information into the boxes. The form will be automatically processed – if you alter its structure your submission will not be processed correctly.

Do not include keywords – you can add them when you submit the abstract online.

Because the amount of demolition waste is large, contractors may think it is worthy to take actions to sort and recycle the demolition waste, and reuse the waste materials at a large scale. It is evident that the most important motivation for contractors to conduct waste reduction is economic profits, followed by BEAM credits. Once the recycling actions are taken, they may pay great efforts. Then, the recycling technologies may come into effect: the better recycling work, the higher award.

Conversely, the construction amount is small, which makes contractors may pay less attention to it due to far less economic profits to take such inconvenient actions. When few projects adopt construction waste recycling, it is understandable the construction waste management performance shows no specific pattern in Table 3. Another reason could be it is more difficult to conduct construction waste reduction than demolition waste reduction because nowadays the widely adoption of prefabrication has reduced the amount of recyclable construction waste. Even though construction waste is far less than demolition waste, its impact to the environment is also considerable. Strategies are needed to stimulate the reduction of construction waste. On-site sorting activities are crucial for waste reduction. With no obvious economic benefits, building construction participants are reluctant to carry out on-site waste sorting (Poon et al., 2001). Legislations can make on-site waste sorting no matter for construction works be fully implemented. In addition, with advanced construction material, technology and management, the construction waste may be naturally of low generation rate. For example, the construction works with and without prefabrication provisions should be treated differently in the requirements of the attainable credits in construction waste reduction. It is noticed that in BEAM, unlike site aspects, energy use, and indoor environment quality, material aspect where waste reduction are mainly in, the grade of which is only counted in overall grade but not required separately (HKGBC, 2015). It means BEAM allocated very few weighting for demolition and construction reduction. Therefore, BEAM should put a high value to demolition and construction waste reduction, due to its serious degradation to the environment.

Conclusions

This study examines the impact of green building accreditation on C&D waste management performance by comparing the WGRs between BEAM awarded project and ordinary projects, and the WGRs between projects of different BEAM awards. Data analysis is relying on a big dataset of waste disposal records, a database for billing account, and a database for BEAM registered project. The data analysis shows that demolition waste management performance can be improved with the involvement of BEAM awards, and projects with higher awards perform better than those with lower awards. However, the construction waste management performance shows no specific pattern along with the change of assessment results. The results indicate the precondition for construction participants to conduct on-site sorting and recycling is economic benefits. Under this precondition, the performance of waste management follows the rule of paying more efforts to gain more BEAM credits. The profitable nature of demolition waste recycling has driven contractors to conduct waste recycling works, while the relatively small amount of construction waste makes recycling of it have little economic profits. Strategies are raised such as forcing legislations to restrict on-site sorting activities, treating projects applied with advanced construction materials, technology and management differently in construction waste reduction, and BEAM should pay more attention to waste management. This study not only reflect the real impact of BEAM for C&D waste management, it is also a reference for policy makers to upgrade their practices in C&D waste management and green building.

References

- EC (2015). Construction and Demolition Waste (CDW). http://ec.europa.eu/environment/waste/construction_demolition.htm, accessed on 12 September 2015.
- EPA (2009). Estimating 2003 Building-related Construction and Demolition Materials Amounts. <http://www.epa.gov/wastes/conserve/imr/cdm/pubs/cd-meas.pdf>, accessed on 21/09/2015.
- HKEPD (2015a). Hong Kong Waste Treatment and Disposal Statistic. http://www.epd.gov.hk/epd/english/environmentinhk/waste/data/stat_treat.html, accessed on 21/09/2015.
- HKEPD (2015b). An overview of challenges for waste reduction and management in Hong Kong. http://www.epd.gov.hk/epd/english/environmentinhk/waste/waste_maincontent.html, accessed on 21/09/2015.

Important notes:

Do **NOT** write outside the grey boxes. Any text or images outside the boxes **will** be deleted.

Do **NOT** alter the structure of this form. Simply enter your information into the boxes. The form will be automatically processed – if you alter its structure your submission will not be processed correctly.

Do not include keywords – you can add them when you submit the abstract online.

HKEPD (2015c). Construction Waste Disposal Charging Scheme. <http://www.epd.gov.hk/epd/misc/cdm/scheme.htm>, accessed on 22/09/2015.

Li, H., Chen, Z., Yong, L., & Kong, S. C. (2005). Application of integrated GPS and GIS technology for reducing construction waste and improving construction efficiency. *Automation in Construction*, 14(3), 323-331.

Lu, W., and Tam, V. W. (2013). Construction waste management policies and their effectiveness in Hong Kong: A longitudinal review. *Renewable and Sustainable Energy Reviews*, 23, 214-223.

Lu, W., and Yuan, H. (2013). Investigating waste reduction potential in the upstream processes of offshore prefabrication construction. *Renewable and Sustainable Energy Reviews*, 28, 804-811.

Osmani, M., Glass, J., and Price, A. D. (2008). Architects' perspectives on construction waste reduction by design. *Waste Management*, 28(7), 1147-1158.

Poon, C. S., Ann, T. W., and Ng, L. H. (2001). On-site sorting of construction and demolition waste in Hong Kong. *Resources, conservation and recycling*, 32(2), 157-172.

Shen, L.Y., Tam, V.W.Y., Tam, C.M. and Drew, D. (2004). Mapping approach for examining waste management on construction sites. *Journal of Construction Engineering and Management*, 130(4), 472-481.

Tam, V. W., & Tam, C. M. (2006). A review on the viable technology for construction waste recycling. *Resources, Conservation and Recycling*, 47(3), 209-221.

Wang, J., Li, Z., & Tam, V. W. (2014). Critical factors in effective construction waste minimization at the design stage: a Shenzhen case study, China. *Resources, Conservation and Recycling*, 82, 1-7.